

exciters/all-in-one transmitters

- > *Easy maintenance exciter series*
- > *All-in-One transmitter series*
- > *All-in-One high fidelity series*

TEX2500LCD



TEX2500LCD front view

Features

- > **PRIMARY APPLICATION:** high quality at a very attractive price. Ideal for use as transmitters in stand-alone applications. Adjustable power output from 10 to 100%.
- > **AUDIO PERFORMANCE:** low distortion and intermodulation values and a high noise/signal ratio.
- > **HARDWARE FEATURES:** compact and indeformable thanks to the stainless steel chassis, in 3 rack units only.
- > **USER-FRIENDLY FEATURES:** four pushbuttons for user/device interaction and software that offers a simple, intuitive interface.
- > **EASE OF MAINTENANCE:** advanced module engineering ensures extreme ease of access and simple maintenance.
- > **OPERATING EFFICIENCY:** incorporate a PFC (Power Factor Corrector) power supply, that provides the utmost efficiency for enhanced energy saving and environmental protection, which added to LD-MOSFET technology ensure high efficiency, better than 70% across the bandwidth.
- > **RELIABILITY/CONTINUITY:** APC (Automatic Power Control) and Foldback protection ensure reliable operation under any operating conditions.
- > **INTERFACE CONTROL:** total control thanks to microprocessor easily programmed from menu with all key parameters displayed on LCD.
- > **INPUT/OUTPUT INTERFACE:** built-in high-performance stereo coder, L&R analogue audio inputs, Mono inputs, MPX composite signal and auxiliary inputs for SCA / RDS signals.
- > **RDS APPLICATION:** built-in RDS encoder with UECP standard functions (option).
- > **REMOTE CONTROL:** built-in telemetry system via GSM modem, battery and battery charger or via WEB or via SNMP (option).
- > **REGULATORY COMPLIANCE:** state-of-the-art technology in full compliance with EC, FCC and CCIR standards.

Caratteristiche

- > **PRIMARY APPLICATION:** alta qualità ad un prezzo estremamente contenuto, ideali come trasmettitori in applicazioni stand-alone con potenza di uscita regolabile dal 10 al 100%.
- > **AUDIO PERFORMANCE:** bassi valori di distorsione, di intermodulazione e alto rapporto segnale rumore.
- > **HARDWARE FEATURES:** compatto, indeformabile e leggero perché realizzati in chassis di acciaio inox, in sole 3 unità rack.
- > **USER-FRIENDLY FEATURES:** quattro tasti a pressione per l'interazione fra l'utente e l'apparato unita ad un software intuitivo e semplificato.
- > **EASE OF MAINTENANCE:** estrema accessibilità e semplicità di manutenzione grazie ad una avanzata ingegnerizzazione modulare dell'apparato.
- > **OPERATING EFFICIENCY:** per un risparmio di risorse energetiche e ambientali, utilizzano un alimentatore PFC (Power Factor Corrector) che sommato alla tecnologia LD-MOSFET garantisce rendimenti elevati, superiori al 70% su tutta la banda.
- > **RELIABILITY/CONTINUITY:** elevata continuità di esercizio garantita in qualsiasi condizione di lavoro attraverso un controllo automatico APC ed una protezione di Foldback.
- > **INTERFACE CONTROL:** controllo completo basato su microprocessore e da menu con lettura su display LCD di tutti i parametri principali.
- > **INPUT/OUTPUT INTERFACE:** stereo coder integrato ad elevate prestazioni, ingressi audio analogici L&R, Mono e segnale composto MPX ed ausiliari per segnali SCA / RDS.
- > **RDS APPLICATION:** encoder RDS integrato UECP standard (versione vendibile opzionalmente).
- > **REMOTE CONTROL:** sistema di telemetria integrato via modem GSM, batteria e caricabatteria o via WEB o via SNMP (versione vendibile opzionalmente).
- > **REGULATORY COMPLIANCE:** tecnologia moderna e pienamente rispondente alle normative EC, FCC ed CCIR.

exciters/all-in-one transmitters

BROADCAST
EQUIPMENT

(Oirt, JPN &
China Band
others
on request)

Technical specifications

Parameter		TEX2500LCD	Value
GENERALS			
Frequency range			FCC - CCIR - OIRT - JPN - CHN
Rated output power			2500 W
Modulation type			Direct carrier frequency
Operational Mode			Mono, Stereo, Multiplex
Environmental working conditions			-10 °C to + 50 °C / 95% relative Humidity non condensing
Frequency programmability			From software, with 10 kHz steps
Frequency stability	WT from -10°C to 50°C		±1 ppm
Modulation capability			150 kHz Stereo, 180 kHz Mono/MPX
Pre-emphasis mode			0 μS, 50 μS (CCIR), 75 μS (FCC)
POWER REQUIREMENTS			
AC Power Input	AC Supply Voltage		230 ±15% VAC
	Active Power Consumption		3571 W
	Overall Efficiency		typical 70 %
	Connector		Terminal Block
MECHANICAL DIMENSIONS			
Physical Dimensions	L x H x W		483 mm x 132 mm x 675 mm
Weight			about 31 kg
Cooling			Forced, with internal fan
Acoustic Noise			< 75 dBA
AUDIO INPUTS			
Left/Mono & Right			10 kOhm or 6000hm (XLR F) Level:-13 to +13 dBu
MPX			10 kOhm or 50 Ohm (BNC) Level: -13 to +13 dBu @ 75 KHz FM
SCA/RDS			10 kOhm (2x BNC) Level: -8 to +13 dBu @ 75 KHz FM
AES/EBU (OPTIONAL)			110 Ohm (XLR F)
TOSLINK (OPTIONAL)			TOSLINK F05 - EIAJ
OUTPUTS			
RF Output			50 Ohm (7/8" EIA flange type)
RF Monitor			50 Ohm (BNC) approx. -60 dBc
Pilot output			>5 kOhm (BNC) approx.1Vpp
FUSES			
On Mains			2 External fuse F 25 T - 10x38 mm
On Service			1 External fuse F 3,15 T - 5x20 mm
On Module Supply			4 Internal fuses F 25 A 10 x 38 mm

All pictures are RVR's property and they are only indicative and not binding. The pictures can be modified without notice.
These are general specifications. They show typical values and are subject to change without notice.

CE 99/5/CE Revision: 06/15

Ordering Information

Code -Codice	Description - Descrizione
Options for TEX2500LCD – Opzioni per TEX2500LCD	
/AUDIGIN-TEX	AES/EBU audio input option for TEX LCD Series. <i>Opzione ingresso audio AES/EBU per famiglia TEX LCD.</i>
/CW	Morse-coded station ID code generated through FSK (Frequency Shift Keying) function. * <i>Codice identificativo della radio via codice Morse attraverso la funzione FSK (Frequency Shift Keying). *</i>
/RDS-TEX3HE	Built-in RDS system with standard basic functions. <i>Sistema RDS integrato con funzioni base standard.</i>
/TLC-TEX3HE	Internal telemetry system without modem. <i>Sistema di telemetria interna senza modem.</i>
/TLM-TEX3HE	Telemetry system via internal GSM modem. Battery and battery charger included. <i>Sistema di telemetria attraverso modem GSM interno. Batteria e caricabatterie incluso.</i>
/TLW-E-TEX3HE	Basic telemetry system via the Internet. <i>Sistema di telemetria di base attraverso internet.</i>
/TLW-TEX3HE	Telemetry system via the Internet. Battery and battery charger included. <i>Sistema di telemetria attraverso internet. Batteria e caricabatterie incluse.</i>

* Please specify station name on order.
Si prega di specificare il nome della stazione in fase di ordine d'acquisto.